




Ref. **6644**

FRESA FRONTALE A SGROSSARE IN HSS-PMX con rompitruciolo tondo fine NZ



IZARMAX



* su richiesta possono essere fornite con raggio di raccordo (corner radius)

Material		Vc		Refs. 6644-6696 Avances fz*/rev. (mm/min.) Feed / Pas								
Grupo	Sub.	PMX	TIALN-TOP	Ø 6	Ø 8	Ø 10	Ø 12	Ø 16	Ø 20	Ø 25	Ø 32	
P	P.2	30-42	45-75	0,030	0,035	0,058	0,069	0,115	0,115	0,115	0,115	
	P.3	12-18	20-35	0,025	0,030	0,052	0,052	0,075	0,075	0,075	0,075	
	P.5	18-24	30-45	0,025	0,030	0,052	0,052	0,075	0,075	0,075	0,075	
S		18-24	30-45	0,042	0,062	0,077	0,092	0,127	0,150	0,150	0,150	

$$* vf \text{ (mm/min.)} = r.p.m. \times Z \times fz \times K$$

(K = Coeficiente Corrección / Correction Coefficient / Coefficient de Correction)

$$Vc = m/min.$$

$$r.p.m. = \frac{Vc \times 1.000}{\pi \times \phi}$$

D	d	L	l	Z
mm	mm	mm	mm	
6,00	6	57	13	4
7,00	10	66	16	4
8,00	10	69	19	4
9,00	10	69	19	4
10,00	10	72	22	5
12,00	12	83	26	5
14,00	12	83	26	5
16,00	16	92	32	5
18,00	16	92	32	5
20,00	20	104	38	5
22,00	20	104	38	5
25,00	25	121	45	5
28,00	25	121	45	5
30,00	25	121	45	5
32,00	32	133	53	6

N° Art
TIALN-TOP

45529
23140
45532
23141
45535
45537
45538
45540
45543
45546
14880
45549
12822
14883
45248