



HARTNER


Punte elicoidali, extra corte

Articolo nr. 81173

P	M	K	N	S	H
○	●		○	○	



punta per INOX • spoglia sul cono tagliente • acciaio HSS legato al Co • massima resistenza all'usura
acciai inossidabili, resistenti al calore ed austenitici (V2A e V4A)



d1 mm	l1 mm	l2 mm	d1 mm	l1 mm	l2 mm
1,000	26,000	6,000	5,600	66,000	28,000
1,100	28,000	7,000	5,800	66,000	28,000
1,200	30,000	8,000	5,900	66,000	28,000
1,300	30,000	8,000	6,000	66,000	28,000
1,400	32,000	9,000	6,100	70,000	31,000
1,500	32,000	9,000	6,300	70,000	31,000
1,600	34,000	10,000	6,500	70,000	31,000
1,700	34,000	10,000	6,600	70,000	31,000
1,800	36,000	11,000	6,700	70,000	31,000
2,000	38,000	12,000	6,800	74,000	34,000
2,100	38,000	12,000	6,900	74,000	34,000
2,200	40,000	13,000	7,000	74,000	34,000
2,300	40,000	13,000	7,100	74,000	34,000
2,400	43,000	14,000	7,400	74,000	34,000
2,500	43,000	14,000	7,500	74,000	34,000
2,600	43,000	14,000	7,600	79,000	37,000
2,700	46,000	16,000	7,800	79,000	37,000
2,800	46,000	16,000	7,900	79,000	37,000
2,900	46,000	16,000	8,000	79,000	37,000
3,000	46,000	16,000	8,100	79,000	37,000
3,100	49,000	18,000	8,200	79,000	37,000
3,200	49,000	18,000	8,500	79,000	37,000
3,300	49,000	18,000	8,700	84,000	40,000
3,400	52,000	20,000	9,000	84,000	40,000
3,500	52,000	20,000	9,200	84,000	40,000
3,600	52,000	20,000	9,500	84,000	40,000
3,800	55,000	22,000	10,000	89,000	43,000
3,900	55,000	22,000	10,200	89,000	43,000
4,000	55,000	22,000	10,500	89,000	43,000
4,100	55,000	22,000	11,000	95,000	47,000
4,200	55,000	22,000	11,500	95,000	47,000
4,300	58,000	24,000	12,000	102,000	51,000
4,500	58,000	24,000			
4,600	58,000	24,000			
4,700	58,000	24,000			
4,800	62,000	26,000			
4,900	62,000	26,000			
5,000	62,000	26,000			
5,100	62,000	26,000			
5,200	62,000	26,000			
5,300	62,000	26,000			
5,500	66,000	28,000			