

## Cesoie per lamiera a leva

Erdi

### Cesoia Mod. Ideal



| N°       | ←a→ |        | ←b→ |        | ↓max.↑<br>mm | ⚙️ | ⚖️<br>kg | 📦<br>Pz. | V4 |
|----------|-----|--------|-----|--------|--------------|----|----------|----------|----|
|          | mm  | "      | mm  | "      |              |    |          |          |    |
| D27A     | 260 | 10 1/4 | 33  | 1 5/16 | 1,2          | ++ | 0,56     | 5        |    |
| D27AL    | 260 | 10 1/4 | 33  | 1 5/16 | 1,2          | ++ | 0,56     | 5        |    |
| D27A-SB  | 260 | 10 1/4 | 33  | 1 5/16 | 1,2          | ++ | 0,57     | 5        |    |
| D27AL-SB | 260 | 10 1/4 | 33  | 1 5/16 | 1,2          | ++ | 0,57     | 5        |    |



- Per tagli passanti diritti e sagomati
- Lame con microdentatura per evitare lo slittamento
- Disponibile per taglio destro e sinistro

### Cesoia per taglio sagomato



| N°   | ←a→ |        | ←b→ |        | ↓max.↑<br>mm | ⚙️ | ⚖️<br>kg | 📦<br>Pz. | V4 |
|------|-----|--------|-----|--------|--------------|----|----------|----------|----|
|      | mm  | "      | mm  | "      |              |    |          |          |    |
| D27  | 260 | 10 1/4 | 40  | 1 9/16 | 1,2          | ++ | 0,49     | 5        |    |
| D27L | 260 | 10 1/4 | 40  | 1 9/16 | 1,2          | ++ | 0,49     | 5        |    |



- Per tagli corti diritti e sagomati
- Lame con microdentatura per evitare lo slittamento
- Disponibile per taglio destro e sinistro

### Cesoia per taglio passante



| N°    | ←a→ |        | ←b→ |        | ↓max.↑<br>mm | ⚙️ | ⚖️<br>kg | 📦<br>Pz. | V4 |
|-------|-----|--------|-----|--------|--------------|----|----------|----------|----|
|       | mm  | "      | mm  | "      |              |    |          |          |    |
| D27B  | 260 | 10 1/4 | 32  | 1 5/16 | 1,2          | ++ | 0,56     | 5        |    |
| D27BL | 260 | 10 1/4 | 32  | 1 5/16 | 1,2          | ++ | 0,56     | 5        |    |



- Per tagli passanti dritti
- Lame con microdentatura per evitare lo slittamento
- Disponibile per taglio destro e sinistro