

R6000D-ATS



**AVR ALTERNATOR WITH
100% COPPER WINDINGS**

**OIL ALARM - OVERLOAD
PROTECTION**



BATTERY INCLUDED



ELECTRIC STARTER

R8500D-T FULL POWER



BATTERY INCLUDED



ELECTRIC STARTER



**TROLLEY
INCLUDED**

R6000D-ATS

R8500D-T FULL POWER

Engine model	R420	R500-V
Engine type	Air-cooled, 4-Stroke, OHV, Single cylinder	Air-cooled, 4-Stroke, Single cylinder
Starting system	Recoil / Electric starter	Recoil / Electric starter
Displacement	420 cc	500 cc
Bore x Stroke	90 x 66 mm	90 x 66 mm
Compression ratio	8.5 : 1	8.5 : 1
Rated frequency	50 Hz	50 Hz
Rated voltage	230 V	230 V / 400 V FULL POWER
Rated power	5.5 kW	8 kVA 230 V / 8 kVA 400 V
Max power	6 kW	8.5 kVA 230 V / 8.5 kVA 400 V
DC output	12 V / 8.3 A	12 V / 8.3 A
Fuel tank capacity	25 L	25 L
Full load continuum running time	7 h	7 h
1/2 load continuum running time	11 h	11 h
Noise (7m)	74 dB	72 dB
Dimensions (L x W x H)	683 x 540 x 542 mm	697 x 554 x 549 mm
Net weight	87 kg	104 kg

**Integrated ATS
(Automatic Transfer Switch)
for automatic start in case of
mains failure.**



**OPTIONAL:
Trolley kit on models R6000D-ATS.**

