

SPIT PULSA 40P+



In accordance to:
EN 12549
EN ISO 11148-13
Directive tool :
2006/42/EC
2011/65/UE
1999/5/EC
CEM 2004/108/EC
Fuel cell : 75/324/EC
Battery : 2006/66/EC
Charger :
2006/95/EC
CEM 2004/108/EC

Tool Specifications

Name	SPIT PULSA 40P+
Impact force (Joules)	100
Weight (kg)	3.7 (with battery)
Overall dimension LxH (mm)	396x114x309
Energy	Fuel cell & Battery
Fastener lengths (mm)	15 to 40 mm in strip

Characteristics

Drywall pin guide
Fully automatic tool (1000 shots per hour)
20 pins magazine (10 per strip)
Low push down force (4.5 kg)
Gas & Battery gauges: check gas & battery levels anytime
Start & Go system: energy saving, "self cut-off" when it is not used for 1mn
Automatic gas dosage (used T° - 15 °C to + 49 °C)
Battery charging time: 105 mn (25 mn = 1000 pins)
Fuel cell: 600 shots (20 °C), battery: up to 3500 shots

Safety Specifications

CE marking
Complete tool pressure necessary to generate the shot
Security with on / off led indicator
Noise level, EN 12549 : LpA,1s,1m=95dB(A) / Lp Cpeak=135 dB
Vibration, EN ISO 8662-11: 4.4 m·s ⁻²

Accessories	Consumables
50 pins magazine	C6, HC6,
Magnetic pin guide	Metal washer
Cleaning kit	